



2024 CRF250R SPECIFICATIONS*

ENGINE	
Engine Type	249cc liquid-cooled single-cylinder four-stroke
Bore and Stroke	79.0mm x 50.9mm
Compression Ratio	13.9:1
Valve Train	DOHC, four valves per cylinder
Induction	Programmed Fuel-Injection system (PGM-FI); 44mm throttle bore
DRIVETRAIN	
Transmission	Five-speed
Final Drive	#520 Chain; 13T/50T
CHASSIS SUSPENSION BRAKES	
Front Suspension	49mm leading-axle inverted Showa® SPG coil-spring fork with rebound- and compression-damping adjustability; 12.2-inch travel
Rear Suspension	Pro-Link Showa single shock with spring preload, rebound- and compression-damping adjustability; 12.3-inch travel
Front Brake	Single 260mm disc
Rear Brake	Single 240mm disc
Front Tire	Pirelli Scorpion MX32 80/100-21
Rear Tire	Pirelli Scorpion MX32 100/90-19
DIMENSIONS	
Rake	27.3°
Trail	4.6 inches
Wheelbase	58.1 inches
Seat Height	37.8 inches
Curb Weight	229 pounds (Includes all standard equipment, required fluids and full tank of fuel)
Fuel Capacity	1.7 gallons
Ground Clearance	13.1 inches
OTHER	
Available Colors	Red
Model ID	CRF250R

*All figures are preliminary and subject to change.